



# NTN BEARING-SUDAMERICANA, S.A.



4.724 Inch | 120 Millimeter x 6.496 Inch | 165 Millimeter x 3.465 Inch | 88 Millimeter TIMKEN 3MMC9324WI QUM Precision Ball Bearings

Bearing No. 3MMC9324WI QUM

3MMC9324WI QUM Bearing 2D drawings and 3D CAD models

|                      |   |
|----------------------|---|
| Category             | Precision Ball Bearings   |
| Inventory            | 0.0   |
| Manufacturer Name    | TIMKEN  |
| Minimum Buy Quantity | N/A   |
| Weight               | 4.98  |
| EAN                  | 0087796353312   |
| Product Group        | B04270  |
| Enclosure            | Open  |
| Precision Class      | ABEC 7   ISO P4   |
| Material - Ball      | Ceramic   |
| Number of Bearings   | 4 (1 Quadruplex Set)  |
| Contact Angle        | 25 Degree   |
| Preload              | Medium  |
| Raceway Style        | 1 Rib Outer Ring  |
| Cage Material        | Phenolic  |
| Rolling Element      | Ball Bearing  |
| Mounting Arrangement | Quadruplex-Universal  |
| Flush Ground         | Yes   |
| Inch - Metric        | Metric  |
| Other Features       | Single Row   Angular Contact   Super High Precision   Hybrid   Corrosion Resistant Ball |
| Long Description     | 120MM Bore; 165MM Outside Diameter; 88MM Width; Open Enclosure;                         |



## NTN BEARING-SUDAMERICANA, S.A.

|                          |  |
|--------------------------|--|
|                          | ABEC 7   ISO P4 Precision;<br>Ceramic Ball Material; 4 (1<br>Quadruplex Set) Bearings;<br>25 Degree Contact Angle;<br>Phenolic Cage Material; 1<br>Rib |
| Category                 | Precision Ball Bearings  |
| UNSPSC                   | 31171531   |
| Harmonized Tariff Code   | 8482.10.50.28  |
| Noun                     | Bearing  |
| Keyword String           | Angular Contact Ball   |
| Manufacturer URL         | <a href="http://www.timken.com">http://www.timken.com</a>  |
| Manufacturer Item Number | 3MMC9324WI QUM   |
| Weight / LBS             | 10.96  |
| d                        | 4.724 Inch   120 Millimeter  |
| D                        | 6.496 Inch   165 Millimeter  |
| B                        | 3.465 Inch   88 Millimeter   |